



# ELECTRIC 6-YEAR



- Available in 28- to 55-gallon nominal capacity
- Tall, Short, Lowboy and Table Top models available
- Dual 4500 Watt Heating Elements for most models
- PEX dip tube helps reduce sediment build-up and maintain efficiency
- Glass-lined tank with anode rod protects against corrosion
- Factory-Installed temperature and pressure (T&P) relief valve
- 6-year tank and parts limited warranty, 1-year limited labor warranty†
- All residential electric water heaters are compliant with HUD standards for mobile homes/manufactured housing

Product Type	Model Number	Nominal Capacity (Gallons)	Rated Storage Volume (Gallons)	First Hour Delivery (Gallons)	Element Wattage (Standard)	Recovery 90° Rise - (Gallons per Hour)	Uniform Energy Factor	Diameter (Inches)	Height to top of tank (Inches)
<b>6-Year Limited Warranty Tank/Parts, 1-Year Limited Warranty Labor†</b>									
Tall	6 55 EORT	55	55	72	4500/4500	21	0.93	24	56 1/2
Tall	6 50 EOHRT	50	46	62	5500/5500	25	0.92	20 1/2	59
Tall	6 50 EORT*	50	46	62	4500/4500	21	0.92	20 1/2	59
Short	6 50 EOHRS	50	46	57	5500/5500	25	0.92	23	49 1/4
Short	6 50 EORS*	50	46	57	4500/4500	21	0.92	23	49 1/4
Lowboy	6 50 EOLS*	51	48	51	4500/4500	21	0.92	26 1/2	36
Tall	6 40 EOHRT	40	36	53	5500/5500	25	0.92	18	61 1/4
Tall	6 40 EORT*	40	36	53	4500/4500	21	0.92	18	61 1/4
Short	6 40 EOHRS	40	37	55	5500/5500	25	0.92	20 1/2	50
Short	6 40 EORS*	40	37	55	4500/4500	21	0.92	20 1/2	50
Short	6 40 EORSS	40	37	55	4500	21	0.92	20 1/2	50
Lowboy	6 40 EOMS**	38	35	54	4500/4500	21	0.93	26	33 1/2
Lowboy	6 40 EOLS	38	35	50	4500/4500	21	0.89	26	33 1/2
Table Top	6 38 EOTT	38	35	55	4500/4500	21	0.90	24 x 25	36
Lowboy	6 36 EOLS*	36	33	51	4500/4500	21	0.92	24	32
Tall	6 30 EORT*	30	27	48	4500/4500	21	0.89	19	46 1/2
Short	6 30 EORS*	30	27	47	4500/4500	21	0.89	22	39 3/4
Short	6 30 EORSS	30	27	47	4500	21	0.89	22	39 3/4
Lowboy	6 30 EOLS*	28	26	44	4500/4500	21	0.90	24	31 1/4
<b>6-Year Limited Warranty Tank/Parts, 1-Year Limited Warranty Labor†, Shipped with Factory Insulation Blanket</b>									
Lowboy	6 50 EOLBS	48	44	60	4500/4500	21	0.93	26 1/2	34
Lowboy	6 40 EOMBS E**	38	35	57	4500/4500	21	0.94	24	31 3/4
Lowboy	6 40 EOLBS*	38	35	51	4500/4500	21	0.92	23	32
Short	6 30 EORBS	30	27	50	4500/4500	21	0.90	20	39 1/4
Lowboy	6 30 EOLBS*	28	26	43	4500/4500	21	0.89	20	30



†For complete information consult written warranty.

\*Add "G" to end of model number for top T&P configuration. Example: 6 30 EORT becomes 6 30 EORT G.

\*\*Side water connections.

Reliance® Water Heater Company reserves the right to make product changes or improvements without prior notice. Dimensions, specifications and appearance subject to change without notice in accordance with our policy of continuous product improvement. Some models may not be available in all markets.