





## **ELECTRIC WATER HEATERS**

Product Type	Model Number	Tank Size Gallons	First Hour Rating	Electric Input Watts/ Hour	Recovery 90° Rise - Gallons/ Hour	Energy Factor	Height (inches)	Diameter (inches)	Est. Annual Cost of Operation	
Hybrid Electric	Heat Pump, 10-Year	Limited Warra	anty Tank/F	arts, 1-Year Li	mited Warranty	Labor†				
Tall	10 50 DHPST	50	68	4500	21	2.75	63	22	\$192	
Tall	10 66 DHPST	66	81	4500	21	2.74	61	26 1/2	\$192	
Tall	10 80 DHPST	80	91	4500	21	2.72	69	26 1/2	\$194	
12-Year Limite	12-Year Limited Warranty Tank/Parts, 1-Year Limited Warranty Labor <sup>†</sup> , Electronic Thermostat, Touch-Screen Display									
Medium	12 40 EARS	40	56	5500	25	.95	50	22	\$555	
Medium	12 50 EARS	50	58	5500	25	.95	49 3/4	24	\$555	
Tall	12 40 EART	40	61	5500	25	.95	60 1/4	20	\$555	
Tall	12 50 EART	50	79	5500	25	.95	60 1/2	22	\$555	
9-Year Limited	Warranty Tank/Part	s, 1-Year Lim	ited Warra	nty Labor <sup>†</sup> , Ele	ectronic Therm	ostat				
Medium	9 40 EKRS	40	56	4500	21	.95	50	22	\$555	
Tall	9 40 EKRT	40	61	4500	21	.95	60 1/4	20	\$555	
Medium	9 50 EKRS	50	58	4500	21	.95	49 3/4	24	\$555	
Tall	9 50 EKRT	50	79	4500	21	.95	60 1/2	22	\$555	
6-Year Limited	Warranty Tank/Part	s, 1-Year Lim	ited Warra	nty Labor <sup>†</sup> , Mo	echanical Theri	nostat				
Lowboy	6 30 EOLS	28	41	4500	21	.95	31 1/4	24	\$555	
Medium	6 30 EORS	30	43	4500	21	.95	39 3/4	22	\$555	
Tall	6 30 EORT	30	43	4500	21	.95	46 1/2	19	\$555	
Lowboy	6 40 EOMS	38	44	4500	21	.95	33 1/2	26	\$555	
Table Top	6 40 2OT4	38	45	4500	21	.88	36	24 x 25	\$599	
Medium	6 40 EORS	40	54	4500	21	.95	50	22	\$555	
Tall	6 40 EORT	40	51	4500	21	.95	60 1/4	20	\$555	
Medium	6 50 EORS	50	62	4500	21	.95	49 3/4	24	\$555	
Tall	6 50 EORT	50	69	4500	21	.95	60 1/2	22	\$555	
Compact	6 6 SOMS K∆	6	N/A	1650	8	N/A	15 1/4	14 1/4	N/A	
Compact	6 10 SOMS K∆	10	N/A	1650	8	N/A	18 1/4	16	N/A	
Compact	6 20 SOMS K*∆	19	N/A	1650	8	N/A	25	18	N/A	
Compact	6 30 EOMSS K**∆	28	40	1650	8	.95	31 1/4	24	\$555	
6-Year Limited	Warranty Tank/Part	s, 1-Year Lim	ited Warra	nty Labor <sup>†</sup> , Mo	echanical Theri	mostat, Shi	pped with F	actory Insula	ation Blanket	
Mobile Home	6 30 EMHBS	30	43	3800	17	.95	39	20	\$555	
Lowboy	6 30 EOLBS	28	40	4500	21	.95	30	22	\$555	
Medium	6 30 EORBS	30	43	4500	21	.95	39	20	\$555	
Compact	6 30 EOMBS K△	28	40	1650	8	.95	30	22	\$555	
Compact	6 30 EOMBS E	28	40	4500	21	.95	30	22	\$555	
Tall	6 50 EORBT	50	69	4500	21	.95	60 1/4	21	\$555	
Lowboy	6 40 EOLBS	38	46	4500	21	.95	31 3/4	24	\$555	
Point-of-Use, 6	6-Year Limited Warra	inty Tank/Pa	rts, 1-Year	Limited Warra	nty Labor†					
Point-of-Use	6 2 SSUS K△	2.5	N/A	1500	7	N/A	13 3/4	13 3/4 x 11	N/A	
Mobile Home,	6-Year Limited Warr	anty Tank/Pa	rts, 1-Year	Limited Warra	anty Labor <sup>†</sup>					
Mobile Home	6 40 EMHSD	40	52	3800	17	.95	50	22	\$555	



## **ENERGY STAR® Qualified Models**

\*Compact models - change "K" to "E" for 240V/2000W elements.

\*\*Models 6 30 EOMSS K and 6 30 EOMBS K - change "K" to "E" for 240V/4500W element.

\*For complete information consult written warranty.

^Configured for 120V AC power.

\*Energy Factor ratings shown for Hybrid Electric Heat Pump units are based on operation in the Hybrid mode. Recovery Ratings shown for Hybrid Electric Heat Pump units are

based on back up heating element performance.

Models shipped from the factory with an insulation blanket have a "B" as the second to last character in the model number not counting the voltage designation letters K and E for compact models. For example: 6 30 EOLBS, 6 30 EOMBS K, or 6 30 EOMBS E. Not all models have derivatives with factory supplied insulation blankets, see section of table above for models available with an insulation blankets.

Reliance® Water Heater Company reserves the right to make product changes or improvements without prior notice. Dimensions in all charts shown in inches. Dimensions and specifications subject to change without notice in accordance with our policy of continuous product improvement. Some models may not be available in all markets. See written warranty for complete details.









## GAS WATER HEATERS (Available in Natural Gas or Propane)

	Product Type	Model Number	Tank Size Gallons	First Hour Rating	Natural Gas‡ BTU Input	Recovery 90° Rise - Gallons/ Hour	Energy Factor	Height Δ (inches)	Diameter (inches)	Est. Annual Cost of Operation
	High Efficiency, 12	- & 6-Year Limited Wa	rranty Tank/F	arts, 1-Yea	ar Limited Warra	nty Labor† (No	t for Mobile	e Home Use)		
	Tall	12 40 GPCT*	40	70	40,000	43	.70	61 1/2	20	\$233
	Tall	12 50 GPCT*	50	81	40,000	43	.70	60 1/2	22	\$233
	Tall	6 40 GBFT	40	67	40,000	41	.67	64 1/4	20	\$244
	Short	6 40 GBFS	40	67	40,000	41	.67	54	22	\$244
	Tall	6 50 GBFT	50	81	40,000	41	.67	63 1/2	22	\$244
	12-Year Limited Wa	arranty Tank/Parts, 1-	Year Limited \	Warranty L	abor <sup>†</sup> , Standard	Vent (Not for I	Mobile Hon	ne Use)		
	Short	12 40 NACS*	40	68	40,000	41	.62	51 1/2	22	\$263
	Tall	12 40 NACT	40	70	40,000	41	.62	62	20	\$263
	Tall	12 50 NQCT*	50	92	50,000	58	.60	60 3/4	22	\$272
	Tall	12 50 NACT	50	88	40,000	41	.62	60 3/4	22	\$263
Ş	9-Year Limited Wa	rranty Tank/Parts, 1-Y	ear Limited W	arranty La	bor <sup>†</sup> , Electronic	Thermostat				
	Tall	9 40 NKCT	40	70	40,000	41	.62	62	20	\$263
	Short	9 40 NKCS	40	68	40,000	41	.62	51 1/2	22	\$263
	Tall	9 50 NKRT	50	88	40,000	41	.60	60 3/4	21	\$272
6	S-Year Limited Wa	rranty Tank/Parts, 1-Y	ear Limited W	arranty La	bor <sup>†</sup> , Mechanica	al Thermostat				
	Short	6 30 NOCS	30	62	35,500	36	.63	50	20	\$259
	Tall	6 30 NOCT	30	67	35,500	36	.63	61 3/4	18	\$259
	Short	6 40 NBCS	40	68	40,000	41	.62	51 1/2	22	\$263
	Tall	6 40 NBCT*	40	70	40,000	41	.62	62	20	\$263
	Tall	6 40 NOCT	40	67	35,500	36	.62	62	20	\$263
	Tall	6 50 NBRT	50	88	40,000	41	.60	60 3/4	21	\$272
	Short	6 75 XRRS	74	N/A	75,100	81	N/A	61	26 1/2	N/A
	Tall	6 100 XRRT	100	N/A	75,100	81	N/A	68 1/2	27 3/4	N/A
6	S-Year Limited Wa	rranty Tank/Parts, 1-Y	ear Limited W	arranty La	bor,† Shipped w	ith Factory Ins	ulation Bla	nket		
	Tall	6 30 NORBT	30	64	35,500	36	.63	61 3/4	16	\$259
	Short	6 30 NORBS	30	56	35,500	36	.63	50	18	\$259
	Short	6 40 NBRBS	40	67	40,000	41	.62	51 1/2	20	\$263
	Tall	6 40 NBRBT	40	70	40,000	41	.62	62	18	\$263
1	Power-Vent, Powe	r Direct-Vent , 6-Year I	imited Warra	nty Tank/F	Parts, 1-Year Lim	nited Warranty	Labor†			
	Power-Vent	6 40 YRVIT	40	90	50,000	56	.70	70 1/4	20	\$233
	Power-Vent	6 50 YRVIT	50	96	50,000	56	.70	69 3/4	22	\$233
١	ery High Efficiend	cy 90% Thermal Effici	ency Power V	ent, 6-Year	Limited Warran	ty Tank/Parts,	, 1-Year Lim	ited Warranty	y Labor <sup>†</sup>	
	Power-Vent	6 50 YTVIT*	50	127	76,000	92	N/A	70 5/8	22	N/A
١	ery High Efficiend	cy 96% Thermal Effici	ency Power D	irect Vent	, 6-Year Limited	Warranty Tank	k/Parts, 1-Y	ear Limited W	arranty Lab	or <sup>†</sup>
	Power Direct-Vent	6 50 YTPDT	50	164	100,000	129	N/A	66 3/4	22	N/A
Ī	Direct-Vent, 6-Year	r Limited Warranty Tai	nk/Parts, 1-Ye	ear Limited	Warranty Labor	r† (Not for Mob	ile Home U	se)		
	Direct-Vent	6 40 YBDS	40	72	38,000	41	.63	64	22	\$259
	Direct-Vent	6 50 YBDS	50	91	40,000	43	.62	73	22	\$263
N		ard-Vent w/ Convertible		-	•	_	-			
	Mobile Home	6 30 NOMT	30	55	35,500	36	.63	61 1/2	18	\$259
	Mobile Home	6 40 NOMT	40	62	35,500	36	.62	61 3/4	20	\$263
N	Mobile Home Direct	-Vent w/ Convertible Co	ntrol for Natura	l or Propan	e Gas, 6-Year Lim	ited Warranty Ta	ank/Parts, 1	-Year Limited V	Varranty Labo	r <sup>†</sup>
	Mobile Home	6 30 MDV	30	49	30,000	31	.63	58	18	\$259
	Mobile Home	6 40 MDV	40	61	32,000	33	.62	58 3/4	20	\$263
Į	Jitra Low N <u>ox (No</u>	t for Mobile Home Use	), 12-Year Li <u>m</u>	nited W <u>arra</u>	anty Tank/ <u>Parts.</u>	1-Year Limited	d Warranty	Labor <sup>†</sup>		
	Tall	12 40 UNACT*	40	71	40,000	41	.63	62	20	\$259
	Tall	12 50 UNACT*	50	91	40,000	42	.62	60 3/4	22	\$263
	Tall	9 40 UNKCT*	40	71	40,000	41	.63	62	20	\$259
	Tall	9 50 UNKCT*	50	91	40,000	42	.62	60 3/4	22	\$263
	Tall	6 30 UNORT*	30	55	33,000	34	.63	61 3/4	16	\$259
	Tall	6 40 UNBCT*	40	71	40,000	41	.63	62	20	\$259
	Short	6 40 UNBCS*	40	69	40,000	41	.62	51 1/2	22	\$263
	Tall	6 50 UNBCT*	50	91	40,000	42	.62	60 3/4	22	\$263
		<u> </u>		N/A	75,100		N/A	62	25 1/4	N/A



For propane gas water heaters, change "G" to "L" or "N" to "P" or "Y" to "H," or "X" to "C,"in the model number. For example: 12 40 PACT, 6 50 HBDS, or 6 75 CRRS.

\*Not available in propane gas. \$\$\text{Some propane gas models have slightly lower inputs than natural gas models, which may reduce First Hour Rating and recovery by up to 3 gallons on propane models. \$\text{Delight dimension is to the top of the draft diverter.}\$\$ \$\$\$\$\$\$\$\$\$\$\$

Models shipped from the factory with an insulation blanket have a "B" as the second to last character in the model number. For example: 6 30 NORBT or 6 40 NBRBS. Not all models have derivatives with factory supplied insulation blankets, see section of table above for models available with an insulation blankets.

Reliance® Water Heater Company reserves the right to make product changes or improvements without prior notice. Dimensions in all charts shown in inches. Dimensions and specifications subject to change without notice in accordance with our policy of continuous product improvement. Some models may not be available in all markets.