## Reliance.



## GAS Available in Natural Gas or Propane (LP) 6-YEAR FLUE DAMPER

- Available in 40- and 50-gallon nominal capacity
- 6-year tank and parts limited warranty,
  1-year labor limited warranty
- Unique design captures escaping hot combustion gases to retain heated water longer
- Advanced electronic gas control valve assures tighter temperature control
- Glass-lined tank with anode rod protects against corrosion
- Factory-installed PEX polymer lined heat trap nipples
- Factory-installed temperature & pressure (T&P) relief valve



Product Type	Model Number	Nominal Capacity (Gallons)	Rated Storage Volume (Gallons)	First Hour Delivery (Gallons)	Natural Gas‡ BTU Input	Recovery 90° Rise - (Gallons per Hour)	Uniform Energy Factor	Diameter (inches)	Height to Vent Connection (inches)
High Efficiency, 6-Year LImited Warranty Tank/Parts, 1-Year Limited Warranty Labor <sup>†</sup> (Not for Mobile Home Use)									
Flue Damper Tall	6 50 GBFT	50	48	84	40,000	42	0.69	22	63 1/2
Flue Damper Tall	6 40 GBFT	40	38	70	40,000	42	0.64	20	64 1/4
Flue Damper Short	6 40 GBFS	40	38	65	40,000	42	0.66	22	54

For propane gas water heaters, change "G" to "L" or "N" to "P" or "Y" to "H" or "X" to "C" in the model number. For example: 6 50 GBFT becomes 6 50 LBFT.

\$Some propane gas models have slightly lower inputs than natural gas models, which may reduce First Hour Rating and recovery by up to 3 gallons on propane models. For complete information consult written warranty.

Reliance® Water Heater Company reserves the right to make product changes or improvements without prior notice. Dimensions in all charts shown in inches. Dimensions, specifications and appearance subject to change without notice in accordance with our policy of continuous product improvement. Some models may not be available in all markets.