

Reliance

## Reliance.

The Specialty Electric group contains Mobile Home, Compact, and Point-of-Use models.



- All models meet HUD requirements for manufactured housing/mobile home installation
- Side-mounted cold water inlet and hot water outlet for easy installation
- 6-year tank and parts limited warranty
- Glass-lined tank with anode rod protects against corrosion
- Factory-Installed Temperature & Pressure (T&P) Relief Valve



- Ideal for under-counter or crawl space installation
- Inlet and outlet connections on side for easier installation in tight spaces; optional top connection points
- All models 120 volt unless specified otherwise; 1 heating element 2 elements available on 30-gallon models
- 6-year tank and parts limited warranty
- Glass-lined tank with anode rod protects against corrosion
- Factory-Installed Temperature & Pressure (T&P) Relief Valve

## POINT-OF-USE

- For low-demand point-of-use applications, such as a handwashing sink
- 6-year tank; 1-year parts warranty
- Stainless steel heating element
- 120 volt; standard plugged cord

| Product<br>Type | Model<br>Number | Tank<br>Size<br>Gallons | First<br>Hour<br>Rating                        | Elect<br>Inpo          |
|-----------------|-----------------|-------------------------|--|------------------------|
|                 |                 | Reliance                | All mo<br>2 elem<br>6-year<br>Glass-<br>Factor | nents<br>tank<br>lined |
|                 |                 | •                       | Inlet ar<br>space                              | nd ou                  |
|                 | Reliance        |                         |  |                        |

MOBILE HOME

COMPACT

|     | Product<br>Type | Model<br>Number           | Tank<br>Size<br>Gallons | First<br>Hour<br>Rating | Electric<br>Input<br>Watts/<br>Hour | Recovery<br>90° Rise -<br>Gallons/<br>Hour | Energy<br>Factor | Height  | Diameter         | Est.<br>Annual<br>Cost of<br>Operation |
|-----|-----------------|---------------------------|-------------------------|-------------------------|-------------------------------------|--|------------------|---------|------------------|--|
|     | MH              | 6 30 EMHBS <sup>◊</sup>   | 30                      | 44                      | 3800                                | 17   | .95              | 39"     | 20"              | \$555                                  |
|     | MH              | 6 40 EMHSD                | 40                      | 51                      | 3800                                | 17   | .95              | 50"     | 22"              | \$555                                  |
|     | С               | 6 6 SOMS K <sup>∆</sup>   | 6                       | N/A                     | 1650                                | 8  | N/A              | 15 1/4" | 14 1/4"          | N/A                                    |
|     | С               | 6 10 SOMS K <sup>∆</sup>  | 10                      | N/A                     | 1650                                | 8  | N/A              | 18 1/4" | 16"              | N/A                                    |
|     | С               | 6 20 SOMS K*∆             | 19                      | N/A                     | 1650                                | 8  | N/A              | 25"     | 18"              | N/A                                    |
|     | С               | 6 30 EOMSS K**∆           | 28                      | 39                      | 1650                                | 8  | .95              | 31 1/4" | 24"              | \$555                                  |
|     | С               | 6 30 EOMBS K△             | 28                      | 39                      | 1650                                | 8  | .95              | 30"     | 22"              | \$555                                  |
|     | С               | 6 30 EOMBS E <sup>◊</sup> | 28                      | 39                      | 4500                                | 21   | .95              | 30"     | 22"              | \$555                                  |
| . [ | PoU             | 6 2 SSUS K <sup>∆</sup>   | 2.5                     | N/A                     | 1500                                | 7  | N/A              | 11"     | 13 3/4 x 13 3/4" | N/A                                    |

POINT-OF-USE

<sup>\*</sup> Compact models - change "K" to "E" for 240V/2000W element. ♦ Shipped with Factory Insulation Blanket

C = Compact MH = Mobile Home PoU = Point of Use

For complete warranty information consult written warranty.