



HIGH EFFICIENCY

Reliance Water Heaters
Your neighborhood water heater source.



6-Year, Direct-Vent Sidewall Gas

- Single-pipe dual channel system for sidewall venting and intake of combustion air from outside the home
- Can be installed up to 4 feet from outside wall with no electric power
- First Hour Delivery up to 77 gallons
- Piezo igniter allows for easy “one-hand” pilot ignition
- Glass-lined tank with anode rod protects against corrosion
- Eco-Friendly Green Choice® gas burner — reduces NOx emissions by 33%
- Factory-Installed Temperature & Pressure (T&P) Relief Valve

**High Efficiency Direct-Vent Sidewall Gas
6-Year Limited Warranty Tank/Parts, 1-Year Limited Warranty Labor† (Not for Mobile Home Use)**

Profile (Short, Medium, Tall, Lowboy, etc.)	Model Number	Nominal Capacity (Gallons)	Rated Storage Volume (Gallons)	First Hour Delivery (Gallons)	Natural Gas‡ BTU Input	Recovery 90° Rise - (Gallons per Hour)	Uniform Energy Factor	Diameter (inches)	Height to top of draft hood (inches)	Est. Yearly Energy Cost
Direct-Vent Short	6 40 YBDS	40	39	64	38,000	41	0.60	22	67	\$201
Direct-Vent Short	6 50 YBDS	50	48	77	40,000	43	0.66	22	76	\$280

For propane gas water heaters, change “Y” to “H”. For example: 6 40 YBDS would become 6 40 HBDS.

†For complete information consult written warranty. ‡Some propane gas models have slightly lower inputs than natural gas models, which may reduce First Hour Rating and recovery by up to 3 gallons on propane models.

Reliance® Water Heater Company reserves the right to make product changes or improvements without prior notice. Dimensions in all charts shown in inches. Dimensions and specifications subject to change without notice in accordance with our policy of continuous product improvement. Some models may not be available in all markets.