



## GAS Available in Natural Gas or Propane (LP) 12-YEAR



- Available in 40- and 50-gallon nominal capacity
- 12-year tank and parts limited warranty, 1-year labor limited warranty
- Up to 50,000 BTU input
- Electronic gas control valve that provides precise temperature control and operational status
- Self-cleaning PEX dip tube helps reduce sediment build-up and maintain efficiency
- Glass-lined tank with dual heavy-duty anode rods to protect against corrosion
- “Environmentally-Friendly” Non-CFC foam insulation
- Piezo igniter allows for easy “one-hand” pilot ignition without matches
- Factory-installed PEX polymer lined heat trap nipples
- Factory-installed temperature & pressure (T&P) relief valve



Product Type	Model Number	Nominal Capacity (Gallons)	Rated Storage Volume (Gallons)	First Hour Delivery (Gallons)	Natural Gas‡ BTU Input	Recovery 90° Rise - (Gallons per Hour)	Uniform Energy Factor	Diameter (inches)	Height to Vent Connection (inches)	Est. Yearly Energy Cost
<b>12-Year Limited Warranty Tank/Parts, 1-Year Limited Warranty Labor†, Standard Vent (Not for Mobile Home Use)</b>										
Tall	12 50 NQCT*	50	48	89	50,000	51	0.61	22	60 3/4	\$302
Tall	12 50 NACT	50	48	84	40,000	41	0.62	22	60 3/4	\$298
Tall	12 40 NACT	40	38	80	40,000	41	0.66	20	62	\$280
Short	12 40 NACS*	40	38	67	40,000	41	0.59	22	51 1/2	\$205

For propane gas water heaters, change “G” to “L” or “N” to “P” or “Y” to “H,” or “X” to “C,” in the model number. For example: 12 40 PACT becomes 12 40 PQCT.

\*Not available in propane gas. ‡Some propane gas models have slightly lower inputs than natural gas models, which may reduce First Hour Rating and recovery by up to 3 gallons on propane models. †For complete information consult written warranty.

Reliance® Water Heater Company reserves the right to make product changes or improvements without prior notice. Dimensions in all charts shown in inches. Dimensions, specifications and appearance subject to change without notice in accordance with our policy of continuous product improvement. Some models may not be available in all markets.