



GAS Available in Natural Gas or Propane (LP)
9-YEAR



- Available in 40- and 50-gallon nominal capacity
- 9-year tank and parts limited warranty, 1-year labor limited warranty
- Up to 40,000 BTU input
- Electronic gas control valve that provides precise temperature control and operational status
- Self-cleaning PEX dip tube helps reduce sediment build-up and maintain efficiency
- Glass-lined tank with heavy-duty anode rod protects against corrosion
- “Environmentally-Friendly” Non-CFC foam insulation
- Piezo igniter allows for easy “one-hand” pilot ignition without matches
- Factory-installed PEX polymer lined heat trap nipples
- Factory-installed temperature & pressure (T&P) relief valve



Product Type	Model Number	Nominal Capacity (Gallons)	Rated Storage Volume (Gallons)	First Hour Delivery (Gallons)	Natural Gas‡ BTU Input	Recovery 90° Rise - (Gallons per Hour)	Uniform Energy Factor	Diameter (inches)	Height to Vent Connection (inches)	Est. Yearly Energy Cost
9-Year Limited Warranty Tank/Parts, 1-Year Limited Warranty Labor†, Electronic Thermostat										
Tall	9 50 NKRT	50	48	81	40,000	41	0.62	21	60 3/4	\$298
Tall	9 40 NKCT	40	38	80	40,000	41	0.66	20	62	\$280
Short	9 40 NKCS	40	38	67	40,000	41	0.59	22	51 1/2	\$205

For propane gas water heaters, change “G” to “L” or “N” to “P” or “Y” to “H,” or “X” to “C,” in the model number. For example: 9 50 NKRT becomes 9 50 PKRT.

‡Some propane gas models have slightly lower inputs than natural gas models, which may reduce First Hour Rating and recovery by up to 3 gallons on propane models.

†For complete information consult written warranty.

Reliance® Water Heater Company reserves the right to make product changes or improvements without prior notice. Dimensions in all charts shown in inches. Dimensions, specifications and appearance subject to change without notice in accordance with our policy of continuous product improvement. Some models may not be available in all markets.